

Easy Dunker / EconoDunker Maintenance

For both ***Easy Dunkers & EconoDunkers...***

- Periodically, check tank and frame for any sharp edges.
- Check seat hinges, bolts and seat spring to be sure that they are solid and secure. Replace if they show signs of wear.
- Replace any parts that show signs of wear.
- **Do not use Windex** (or any other ammonia-based product) on the dunk tank window. Windows can be easily cleaned using a sponge or cotton cloth, warm water, and a mild dish detergent. The window should be rinsed with cold water and dried with a cotton cloth to reduce water spots. In rare instances in which soap and water are insufficient, the following agents may be used (at room temperature): methyl alcohol, ethyl alcohol, isopropyl alcohol, heptane, hexane, petroleum ether, VM&P naphtha.
- **Do not replace window with Plexiglass.** Note: We have replacement window kits available. If you find it necessary to replace a window, be sure to only use an impact resistant polycarbonate. Anything else will burst on impact, resulting in a dangerous situation.

For ***Easy Dunkers*** (with trailer) only....

- ◆ Check the wiring for the brake lights for any cuts or crimps.
- ◆ Always check brake lights and turns signals, before towing.
- ◆ Check the rope to hold wing frame against tank for wear.
- ◆ Check safety chain and BOTH tongue pins.
- ◆ Replace any parts that show signs of wear.